

KOBE 150mm Random Orbital Sander

FS0150

Suitable for shaping, blending, smoothing body filler and rapid material removal. Rubber handle. Random orbit. Can be used for wet sanding. Rotating air inlet to prevent tangling. Speed control for easy adjustment. Ball bearing construction for a long tool life.

Backing pad size: 150mm (6"). **Backing pad type:** hook and loop.

Orbit diameter: 5mm (3/16"). **Suction type:** Self-generating vacuum.

Spindle size: 5/16" NPT. **Free speed:** 10,000rpm.

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID): 10mm (3/8").

Air pressure: 6.2bar (90psi).

Motor power: 0.2hp.

Air consumption: 3cfm* (85ltr/min).

Overall length: 280mm.



*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code	List Price/1	Offer Price/1	Noise Level	Vibration
10,000	1.04kg	-2720K	£184.00	£128.80	84dBA	5.6m/s

Free Speed (rpm)	Weight each	Order Code	List Price/1	Offer Price/1	Noise Level	Vibration
11,000	1.47kg	-4170K	£191.00	£133.70	88dBA	5.2m/s

KOBE Mini Random Orbital Sander Kit

F05003mk

Uses 2" and 3" backing pads. Rubber handle provides grip and operator comfort. Two finger throttle for easier control and less fatigue. Adjustable power regulator to match the speed to the job. Ball bearing construction for a long tool life.

Accessories included:

2" and 3" backing pads. 10x 2" diameter sanding discs - 320, 400 and 600 grit.

10x 3" diameter sanding discs - 320, 400 and 600 grit. Spindle key and instructions. Supplied in a robust blow-moulded carry case.

Free speed: 15,000rpm.

Air inlet thread: 1/4" NPT.

Minimum air hose size (ID):

3/8" (10mm).

Air consumption: 4cfm*

Vibration level: 0.9m/s².



Free Speed (rpm)	Weight each	Order Code	List Price/1	Offer Price/1
15,000	611g	-2103K	£87.55	£61.29

For Sanding Discs



See Group 280