



Professional Biscuit Joiner

07904

Depth adjustment for standard biscuits - 00, 10, 20 biscuit sizes. Ideal for joining wood at any angle. Faster than using dowels. Designed for precision wood working and furniture making, especially cabinets.



Fine adjustment facility. Fitted with an extremely powerful 700 Watt motor, for maximum performance. Adjustable tilt fence - 0° to 90° for angled biscuit insertion and joints. Dust extraction port for reduction of working environment dust levels. Comes complete in a blow moulded case for storage and protection. Fitted with TCT blade. Two year warranty for extra peace of mind.

Model Number	Voltage	Motor	Weight each	Order Code SIP-277	List Price/1	Offer Price/1
07904	240V	700W	4.70kg	-7904E	£64.90	£55.16

trend Laminated Beech Jointing Biscuits

Biscuit jointing is one of the strongest, fastest, safest and most accurate ways to join hard and soft woods, plywood, MDF and other timbers. Compared to dowelling, biscuit jointing is faster and more precise. The biscuits are made of laminated beech which is then compressed before being die cut. Beechwood biscuits expand when in contact with a woodworking adhesive, e.g. PVA glue.



Price per pack

Size	For Board Thickness	Dimensions (mm)	Pack Qty	Order Code TRE-280	List Price/1	Offer Price/1
No.0	8-12 mm	45x15.5x4.0	100	-2300M	£4.00	£3.68
			1000	-2301P	£20.00	£18.40
No.10	13-18mm	55x20x4.0	100	-2310P	£4.00	£3.68
			1000	-2315Q	£21.00	£19.32
No.20	19mm+	62x23x4.0	100	-2320R	£4.50	£4.14
			1000	-2350V	£22.00	£20.24

DEWALT Planer

D26500K

Power input: 1050W.
Power output: 620W.
No load speed: 13500rpm.
Maximum depth of cut: 4mm.
Rebating depth: 25mm.
Planer width: 82mm.
Shoe length: 320mm.



Accessories
TCT reversible blades, parallel fence, rebate depth guide, dust extraction spout, heavy duty carrying case, deflector and chip collection container, chip ejector.

Voltage	Weight each	Order Code DEW-272	List Price/1	Offer Price/1
110V	4.00kg	-2650K	£315.00	£172.50
240V	4.00kg	-2650R	£315.00	£172.50

BOSCH Planer

NEW

GHO 40-82C

Fitted with 3 V-grooves for easy and flexible chamfering, precise and clearly legible depth of cut setting with workpiece protection and left or right chip clearance. Switch-on lock for left-handers and right-handers. Can also be used as bench-mounted tool with sub-frame.

Power input: 850W
Power output: 450W
No-load speed: 13.500rpm
Planing width: 82mm
Settable chip thickness: 0,0 — 4,0mm
Adjustable rebating depth: 0 — 24mm
Length: 296mm
Width: 169mm
Height: 173mm



Accessories
Rebating depth guide 1 extra Woodrazor reversible blade, 90° parallel guide, Carrying case

Voltage	Weight each	Order Code BCH-266	List Price/1	Offer Price/1
110V	3.20kg	-7405Q	£299.00	£151.00

Makita 1/4" Laminate Trimmer

3703

Power input: 350W.
No load speed: 30,000rpm.
Collet capacity: 1/4".
Base dimensions: 80 x 90mm.
Accessories: Trimmer guide assembly, straight guide assembly, 10mm template guide, 6mm diameter TCT straight bit, two wrenches (10 and 17mm), 1/4" collet cone and chip deflector.



FOR ROUTER CUTTERS



See **GROUP 287**

Voltage	Weight each	Order Code MAK-275	List Price/1	Offer Price/1
110V	1.50kg	-2720W	£187.00	£129.50
240V	1.50kg	-2721X	£187.00	£129.50

CONTRACT PRICES AVAILABLE FOR VOLUME PURCHASES

All Prices Exclude V.A.T. © 2008