



Switches & Sockets

Chrome Dimmer Switch

Polished chrome dimmer switch, 1 gang, 2 way, 250W rating. British made.



Rated	Gang	Order Code	Offer Price/1
250W	1	MRM-281 -5580K	£7.33

Dimmer Switch

1 gang, 2 way dimmer switch, rated 250W. British made.



Rated	Gang	Order Code	Offer Price/1
250W	1	MRM-281 -5320M	£5.69

Chrome Plate Switch

Polished chrome finish, 2 gang, 2 way switch. 10 amp rated. British made.



Rated	Gang	Way	Order Code	Offer Price/1
10A	1	2	MRM-281 -5500R	£6.63

Telephone Master Socket

Single, flush mounted, telephone master socket.



Colour	Socket	Order Code	Offer Price/1
White	1	MRM-281 -3620D	£2.03

Chrome Socket Outlets

1 and 2 gang, socket outlets, rated 250W, double pole. British made.



Rated	Gang	Order Code	Offer Price/1
13A	1	MRM-281 -5530T	£6.12
13A	2	MRM-281 -5540V	£7.76

TV Socket

Coaxial socket outlet, 1 gang non-isolated. White.



Colour	Gang	Order Code	Offer Price/1
White	1	MRM-281 -3540W	£1.64

Weatherproof Moulded Enclosure

Outdoor, IP54 rated, enclosure. 15A connector.



Rated	Connector	Order Code	Offer Price/1
IP54	15A	MRM-281 -5300J	£2.18

Weatherproof Sockets

Masterseal range, IP56, 13A, 1 and 2 gang, unswitched sockets. MK Electric.




Rated	Gang	Order Code	Offer Price/1
13A	1	MRM-281 -1480Y	£25.35
13A	2	MRM-281 -1490Z	£48.34



Rubber Cable Protector Systems - Indoor Use

With the introduction of a new EEC Directive, safety in the work place is paramount. Fitting one of Vulcasco's cable protect or systems is not just good sense, it is a priority for caring employers who consider staff well-being. UV stabilised for extended life. Produced from a fire retardant compound conforming to **BS476 Part 7 Class 3**, and its European equivalent **DIN 4102 Part 1 and Class B1**.
Colour: Black (not illustrated).

9.0 Metre Coil Length




Type	Hole Dimensions	Order Code	Offer Price/1
Standard	8 x 14mm	PRO-280 -0041A	£40.35
B	10 x 30mm	PRO-280 -0042A	£59.16
BNC2	25/15mm	PRO-280 -0043A	£70.40

Rubber Cable Protector Systems - Outdoor Use

Specifically designed to resist the harsh environmental conditions of outdoor use. Suitable for all types of industry. Type F is also available with Department of Transport certification for across road applications in conjunction with temporary traffic signals. Designed to protect dangerous heavy duty cables. Conform to **BS476 Part 7 Class 3**, which is equivalent to the European **DIN 4102 Part 1 and Class B1**.

Type F = 9.0 Metre Coil Length
Type FF and FFF = 4.5 Metre Coil Length



Type	Hole Dimensions	Order Code	Offer Price/1
F	23mm dia x 1	PRO-280 -0044A	£132.22
FF	23mm dia x 2	PRO-280 -0045A	£104.95
FFF	23mm dia x 3	PRO-280 -0046A	£119.19